



R60 & PRO

CONTROLLER PRINthead

10" Controller For 6 High Speed TIJ 2.5 Printheads

R60 PRO



TECHNICAL SPECIFICATIONS

Printing Technology	HP TIJ 2.5
Controller Dimensions	305.6 x 200.9 x 64.2 mm
Printhead Dimensions	140.5 x 46 x 80.4 mm (1 Printhead) 140.5 x 80.7 x 92.8 mm (2 Printheads) 140.5 x 111.9 x 105.2 mm (3 Printheads) 140.5 x 142.9 x 117.6 mm (4 Printheads) 140.5 x 209.9 x 142.7 mm (6 Printheads)
Controller Weight	2,750g
Printhead Weight	234.2g
Display	10" LCD Touch Screen
Power Supply	AC 100V–240V, 50/60Hz, DC 24V 9.2A
Resolution	Max 600 DPI
Print Speed	Up to 76m/min at 300 DPI
Print Density	3 levels
Throw Distance	5mm

FEATURES

Wide Range Of Print Types	• Text, Counter • Box/Lot • Datetime • Expiry Date • Julian Date • Shiftcode • Image • Database 1D & 2D Barcodes (Code 11, Code 39, Code 128, EAN, QR, Datamatrix, GS1 Datamatrix)
Printable Height	Maximum 76.2mm / 6 printheads
External Connections	External Sensor, Encoder and Alarm Beacon
Template Length	1.5m
Data base	TXT, CSV
Advanced Features	• Free design in template up to 76.2mm (3-inches) • POD (Print online data) Integrate with other devices (PLC, Camera, Checkweigher) via RJ45 • Real-time Printing • WYSIWYG (what you see is what you get) • Data upload, Backup & Recovery via USB
Printable Characters	Windows true fonts - Free design in template up to 76.2mm (3-inches)
Print Languages	English (default), Vietnamese, Chinese (PRC), Turkish, Korean, Russian, Japanese, Hebrew, Spanish, Thai, Portuguese and Arabic (and others)
System Languages	English (default), German, Vietnamese, Chinese, Korean, Russian, Turkish, Portuguese, Spanish, Polish, Greek and Italian (and others)

PRO PRINTHEADS COMBINATION

Choice of up to 6 independent printheads

